

# SPORTident Card11

May 2015



The SI-Card11 belongs to the third generation of SI-Cards. SI-Cards11 register the data record in 60 ms. This is twice as fast as SI-Card8/9. All full set of card owners personal data can be stored in the chip.

In general SI-Card11 offers a more smart user experience. SI-Card11 features an integrated electronic module. There is an optical feedback signal (flashing LED) indicating the finished registration process. There is exactly one feedback signal cycle from the SI-Station. The next feedback signals will be transmitted by the SI-Card within some seconds. The number and the rhythm of the optical feedback signal can be configured by the user. This feature is supported by SI-Config+.

SI-Card11 feedback signals are powered by battery. Power consumption is very low. Based on calculations there is enough power to activate up to 30,000 flashing cycles. The SI-Card11 features a fall back option. If the battery is empty the device works like the passive SI-Card10. So any risk is eliminated.

SI-Card11 comes with a chromium plated tip and transparent body. The flashing LED illuminates the SI logo in the tip.



## Specifications

	<b>SI-Card11</b>
Model type	Finger stick
Number range	9 000 001 ... 9 999 999
Typical application	Orienteering, adventure and outdoor sports
Data exchange time	60 ms
Clear time	< 0.5 s
Intermediate times	128
Special records	CLEAR, CHECK, START, FINISH
Time format	24h format, day of week, counter for up to 4 weeks
SI-System compatibility	SI-Stations BSF7/8
Firmware Stations	V 5.74 and higher
Operating range	-20°C ... +50°C
Registration feedback signal	Optical (red LED) signal, user configurable
Protection class	IP 67 (DIN EN 60529) - Protection against penetration of dust - Protection against the ingres of water during short-term immersion
Warranty	5 years, except battery
Battery live time	Up to 30,000 flashing cycles
Weight	8 g
Dimensions	71 mm x 19 mm x 8 mm
Colours	Transparent body, chromium plated tip with logo
Customer services	Online reservation service